

THE COMMISSIONER OF PATENTS AND TRADEMARKS  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of -

Inventor(s): RAYMOND M. BROEMMELSIEK

For: Method for Increasing Multimedia Data Accessibility

Enclosed are:

- ☒ Application with ~~executed~~/unexecuted declaration.
- ☒ Seven ( 7 ) sheets of informal/~~formal~~ drawing.
- ☒ Two ~~executed~~/unexecuted verified ~~statement~~/statements to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27, i.e., independent inventor and small business concern
- ☐ Associate Power of Attorney.

The filing fee has been calculated as follows:

For	#Claims Filed	#Claims Extra	Small Entity		Other Than A Small Entity	
			Rate	Fee	Rate	Fee
Basic Fee .....			\$	380	.....	\$ 760
Total Claims	29	-20 =	9	x \$ 9 \$ 81	x \$18 \$	
Indep Claims	8	- 3 =	5	x \$39 \$ 195	x \$78 \$	
Mul Dep Claim Presented.....			x\$130	\$ --	x\$260	\$
			TOTAL	\$ 656	TOTAL	\$

A check in the amount of \$ 656.00 is attached hereto.

The Commissioner is hereby authorized to charge any additional filing fees required under 37 CFR 1.16 associated with this communication or credit any overpayment to Deposit Account No. 02-3690. A duplicate copy of this sheet is enclosed.

The Commissioner is hereby authorized to charge payment of any filing fees under 37 CFR 1.16 for presentation of extra claims during the pendency of this application or credit any overpayment to Deposit Account No. 02-3690. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

Date: 11/16/99  
P.O. Box 19290  
Alexandria, VA 22320-0290  
Telephone (703) 684-6885

By

*Mary Breiner*

Attorney of Record  
MARY J. BREINER, 33,161

jc511 U.S. PTO

09/441231

11/16/99

**VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) and 1.27(b)) - INDEPENDENT INVENTOR**

Applicant or Patentee: Raymond M. BROEMMELSIEK

Application or Patent No.: \_\_\_\_\_

Filed or Issued: \_\_\_\_\_

Title: Method for Increasing Multimedia Data Accessibility

As a below-named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the United States Patent and Trademark Office described in -

- ☒ the specification filed herewith with title as listed above.  
☐ the application identified above.  
☐ the patent identified above.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☐ No such person, concern, or organization exists.  
☒ Each such person, concern or organization is listed below:

NAME Sakertrax Inc.ADDRESS 9815 Carroll Canyon Road, Ste. 203, San Diego, CA 92131

☐ INDIVIDUAL    ☒ SMALL BUSINESS CONCERN    ☐ NONPROFIT ORGANIZATION

NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ INDIVIDUAL    ☐ SMALL BUSINESS CONCERN    ☐ NONPROFIT ORGANIZATION

NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ INDIVIDUAL    ☐ SMALL BUSINESS CONCERN    ☐ NONPROFIT ORGANIZATION

Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Raymond M. Broemmelsiek

Name of Inventor

Name of Inventor

Name of Inventor

Signature of Inventor

Signature of Inventor

Signature of Inventor

Date \_\_\_\_\_

Date \_\_\_\_\_

Date \_\_\_\_\_

Name of Inventor

Name of Inventor

Signature of Inventor

Signature of Inventor

Date \_\_\_\_\_

Date \_\_\_\_\_

**VERIFIED STATEMENT CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) and 1.27(c)) - SMALL BUSINESS CONCERN**

Applicant or Patentee: Raymond M. BROEMMELSTIEK

Application or Patent No.: \_\_\_\_\_

Filed or Issued: \_\_\_\_\_

Title: Method For Increasing Multimedia Data Accessibility

I hereby declare that I am

☐ the owner of the small business concern identified below:☒ an official of the small business concern empowered to act on behalf of the concern identified below:NAME OF SMALL BUSINESS CONCERN Sakertrax Inc.ADDRESS OF SMALL BUSINESS CONCERN 9815 Carroll Canyon Road, Ste. 203, San Diego, CA 92131

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in -

☒ the specification filed herewith with title as listed above.☐ the application identified above.☐ the patent identified above.

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights in the invention must file separate verified statements averring to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization having any rights in the invention is listed below:

☒ No such person, concern, or organization exists.☐ Each such person, concern or organization is listed below:

NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING \_\_\_\_\_

TITLE OF PERSON IF OTHER THAN OWNER \_\_\_\_\_

ADDRESS OF PERSON SIGNING Sakertrax Inc, 9815 Carroll Canyon Rd., Ste. 203, San Diego, CA 92131

SIGNATURE \_\_\_\_\_

DATE \_\_\_\_\_

## METHOD FOR INCREASING MULTIMEDIA DATA ACCESSIBILITY

### FIELD OF THE INVENTION

The present invention relates to a method for increasing multimedia data

5 accessibility and more specifically to increasing the interactivity with images shown on a display device.

### BACKGROUND OF THE INVENTION

While there are a number of computer-based media types that provide interactive

10 3D representations of objects or scenes, none of these media types provides intuitive interaction while being inexpensively produced and lending themselves to Internet content delivery and play back. The Internet's range of media types is driven largely by transmission bandwidth limitations together with the need for new and more compelling content that make use of new media types.

15

Further, the method by which these media types are viewed and interacted with restricts the users to able-bodied people. When viewing an image, visually impaired people can only view the image when using magnification software supplied by a third party. The available magnification software is cumbersome to use when trying to take advantage of multimedia data, especially images. Often  
20 it is desired to magnify only the image; however, third party software does not readily offer this feature. There are two basic types of magnification software: entire display magnification which hides from immediate view a large portion of

the screen, and mouse centered magnification which provides a fixed screen showing an enlarged version of the area around the mouse. These systems provide only a partial solution as the available magnification software does not provide quick access to the program nor is it flexible enough to use alternative  
5 input devices.

The interactive 3D media types available that are compatible with Internet resource limitations (i.e. QuicktimeVR by Apple Corp. and 360 by IPIX Corp.) require labour intensive production or special capture equipment. This increases  
10 the cost of producing these interactive 3D media types. Further, user navigation of these 3D media types uses a mouse, which is not an intuitive navigation tool, especially when viewing images of a scene. Additionally, these media types require media transmission to be completed before viewing or interacting with the media. In cases where the size of the media is large, this creates a long time  
15 delay before the images can be viewed.

Existing immersive virtual reality technologies provide for 3D interactivity but require special head gear or viewing apparatus, or special cameras. In addition, these methods do not provide for low bandwidth transmission and low latency  
20 response to user input.

United States Patent Number 5,574,836, titled "Interactive Display Apparatus and method with Viewer Position Compensation", discloses a system that provides an

intuitive interactive environment for users. However, this system is based on changing the position of an object to be displayed according to the position of the user. As this system is concerned with changing the position of an object, it does not provide a method for intuitive interaction in a 3D environment or viewing a 3D object from a plurality of viewing angles.

#### SUMMARY OF INVENTION

Accordingly, it is an object of the invention to provide a method for intuitively viewing an image or series of images (either multiple views of an object or different images of unrelated objects).

It is a further object of the invention to provide a method which provides intuitive navigation within a 3D environment.

It is another object of the invention to provide a method which provides intuitive navigation of a 3D image without requiring the position of the viewed object to change.

It is an additional object of the invention to provide a method for transmitting and viewing a series of related images that conforms to Internet resource limitations.

It is a further object of the invention to provide a method for viewing and interacting with images from a series of images prior to receiving every image.

It is a further object of the invention to provide an easily accessible, integrated screen display magnification tool.

- 5 In accordance one object of the present invention there is provided a method of displaying a series of images according to a user's position relative to a display screen comprising the steps of: displaying a first image from the series of images, receiving information regarding a change in the user's position relative to the display screen, and displaying a second image from the series of images in  
10 response to the change in the user's position.

- In accordance with another object of the invention there is provided a method of simultaneously receiving, displaying and interacting with a series of images in response to movement of an interactive device comprising the steps of: (a)  
15 receiving for display a first image from the series of images, (b) receiving for display subsequent images from the series of images, and (c) permitting viewing of and interacting with the first image while performing step (b) where interaction with the first image is in response to signals from the interactive device.

- 20 In accordance with a further object of the invention there is provided a method of transmitting a series of images to increase the fidelity of transmission comprising the steps of: compressing a selected first image from the series of images separately compressing each image from the series of images, and progressively

transmitting each compressed image from the series of images in a manner that first transmits the selected first compressed image and then transmits each image from the series of images such that the further each image is from the selected first compressed image the later it is transmitted.

5

In accordance with another object of the invention there is provided a method of increasing the scale of a portion of a displayed object comprising the steps of: providing a perpetual foreground icon for accessing a magnification tool, accessing the magnification tool, tracking movement of an interactive device,  
10 displaying a specified area as an enlarged area, and changing an enlargement power in response to the interactive device while tracking movement and displaying the specified area.

In accordance with yet another object of the invention there is provided a  
15 computer readable medium having stored thereon computer-executable instructions for displaying a series of images according to a user's position relative to a display screen comprising the steps of: displaying a first image from the series of images, receiving information regarding a change in the user's position relative to the display screen, and displaying a second image from the  
20 series of images in response to the change in the user's position.

In accordance with a further object of the present invention there is provided a computer readable medium having stored thereon computer-executable



instructions for simultaneously receiving, displaying and interacting with a series of images in response to movement of an interactive device comprising the steps of: (a) receiving for display a first image from the series of images, (b) receiving for display subsequent images from the series of images, and (c) permitting  
5 viewing of and interacting with the first image while performing step (b) where interaction with the first image is in response to signals from the interactive device.

In accordance with another object of the invention there is provided a computer  
10 readable medium having stored thereon computer-executable instructions for transmitting a series of images to increase the fidelity of transmission comprising the steps of: compressing a selected first image from the series of images, separately compressing each image from the series of images, and progressively transmitting each compressed image from the series of images in a manner that  
15 first transmits the selected first compressed image and then transmits each image from the series of images such that the further each image is from the selected first compressed image the later it is transmitted.

In accordance with another object of the present invention there is provided a  
20 computer readable medium having stored thereon computer-executable instructions for increasing the scale of a portion of a displayed object comprising the steps of: providing a perpetual foreground icon for accessing a magnification tool, accessing the magnification tool, tracking movement of an interactive

device, displaying a specified area as an enlarged area, and changing an enlargement power in response to the interactive device while tracking movement and displaying the specified area.

## 5 BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in greater detail below, including specific examples thereof, with regard to the figures, in which:

Fig. 1A is an illustration of a prior art system used to capture images at various  
10 view angles to comprise the image set used during playback,

Fig. 1B is an illustration of an embodiment of the present invention in which the capture system of Fig. 1A is shown in connection with various display computers,

15 Fig. 2 is a prior art illustration of resulting images from the corresponding image capture view angles,

Fig. 3 is an illustration of a recording system used for automated image capture according to an embodiment of the present invention,

20

Fig. 4 is an illustration of compression and transmission sequence used during transmission of images according to an embodiment of the present invention,

Fig. 5 is an illustration of a computer system that is used to play back the images according to an embodiment of the present invention,

Fig. 6 is a top view illustration of the various head angles that result in display of corresponding images from Fig. 2 according to an embodiment of the present invention, and

Fig. 7 is a screen view of a screen magnification tool.

## 10 DETAILED DESCRIPTION OF INVENTION

Fig. 1A is an image capture system 11 according to the prior art wherein 2-Dimensional images are used to create a simulated, interactive 3-Dimensional environment. The image capture system 11 includes a camera 12 and an object 10 showing various image capture rotation angles 1, 2, 3, 4, 5, 6, 7 that comprise an image set used during playback and a computer 14 used for image formatting. Individual capture rotation angles are shown: a reference angle 1, rightward rotation angles 3, 5, and 7 and leftward rotation angles 2, 4, and 6.

A system 13 according to an embodiment of the present invention shown in Fig. 1B is composed of three segments: image capture 11, image transmission, and image display. The computer 14 functions for packaging the series of images from the image capture system 11 for efficient image transmission. Transmission

links 16 to the computer 14 provide electrical communication to other computers 18 that are equipped for image display.

Fig. 2 is a sample illustration of resulting individual images 20 from the corresponding image capture rotation angles 1, 2, 3, 4, 5, 6, and 7 shown in the image capture system 11 of Fig. 1A. A reference image 21 corresponds to the reference angle 1 shown in Fig. 1A. Leftward rotation images 23, 25, and 27 correspond to leftward rotation angles 3, 5, and 7 respectively. Similarly, rightward rotation images 22, 24, and 26 correspond to rightward rotation angles 2, 4, and 6 respectively. Although only left and right rotation image capture sequences are shown, this method may be extended to account for camera/object rotation angles that displace in the up and down axes as well, generating a mosaic of images.

The camera 12 shown in Figs. 1A and 1B can be moved about the object 10 or the object 10 can be rotated before the camera 12 generating various views 1 to 7 and thus, the corresponding images 20 are captured. The captured images 20 are stored in computer 14.

The image series can also be a dynamic series in which movement occurs. The camera 12 / object 10 spatial relationship may be changed manually or by machine control. Fig. 3 is an illustration of a recording system 37 used for automated image capture. A camera 33 is mounted to a servo-controlled pan and

tilt gimble 34. The servo-controlled pan and tilt gimble 34 is controlled by a computer 36 through an electrical communication media 35 using motion object tracking algorithms which are known in the art. By processing a video signal from the camera 33 delivered to the computer 36 through the electrical communication media 35, the computer 36 controls the servo-controlled pan and tilt gimble 34 again through the electrical communication 35 such that the camera 33 maintains line-of-sight 31 with a moving object 30 having a trajectory 32. In this manner, a sequence of images is captured such as those shown in Fig. 2.

There are several methods available as well that use conventional video cameras, or digital still cameras. For example, a hand-held video camera may be pointed at the subject or scene that is to be captured and processed into a 3D computer image. Once recorded, the images may be edited on a computer as required and then formatted for "playback" by the holographic image user. These images can be edited in the computer 14 (of Fig. 1B) to form a continuous series of images that represent a complete field of view.

#### *Image Transmission*

A series of images (i.e. as shown in Figs. 2 and 4) is first compressed and then each image is transmitted according to its positional relationship with a reference image (i.e. image 21 in Fig. 2 and image 41 in Fig. 4). According to an embodiment of the present invention, the computer 14 connected to the capture camera 12 may be used for packing the series of images for efficient

transmission. As shown in Fig. 1B, the transmission links 16 may optionally provide electrical communication to other computers 18 that are equipped for image display.

5 As shown in Fig. 4, a sequence of images 40 is captured either manually or automatically. After editing, the images 40 are formatted and compressed. The preferred method of compression is carried out such that one image is first selected for compression - typically the reference image 41 in the sequence of images 40. Because of the strong content correlation between the reference  
10 image 41 and outlying rotation image 48 and 49, motion video compression algorithms as are known in the art can be employed on the outlying rotation images 48 and 49 to reduce the data size for improved transmission efficiency. Therefore, a motion compression algorithm is applied separately on outlying leftward rotation image 49 and outlying rightward rotation image 48 of sequence  
15 40 lying on either sided of the reference image 41 where the reference image is the first image to be displayed as data is received for presentation.

A greater amount of data must be transmitted to an image display (i.e. the computers 18 as shown in Fig. 1B) for a 3D presentation of a sequence of  
20 images 40 than that of a single image as the 3D presentation uses several views of an object. Increased data transmission potentially delays the point in time at which the user may view the holographic or 3D nature of the image data. In order to overcome this, formatting and compression are done such that a progressive

approach is used in which a portion of the data may be viewed and interacted with before the entire set of data is received. In order to reduce delay, to provide the user with useful but not necessarily complete information sooner, the following order is used:

5

1) Given that the uncompressed and unformatted representation (raw data) of the holographic image of an object is a series of images 40 of that object, each successive image is captured at a subsequently larger view angle than the first capture image. For purposes of applying known interframe motion compression techniques and for initial viewing of the holographic object image, the reference image 41 (or center image) becomes the reference for the outlying images. This is the first image transmitted.

2) Given that the sequence of images 48 and 49 lying on either side of the reference image 41 exhibit very strong frame-to-frame correlation, interframe motion compression is applied separately to each of the outlying leftward rotation image 49 and outlying rightward image 48 to achieve superior compression ratios.

3) The resulting compressed images from the outlying rightward rotation images 48 and the outlying leftward rotation images 49 are transmitted progressively in an order that allows compressed images further away from the reference image 41 to be transmitted later. Therefore, the compressed images

are ordered alternating left and right side of the reference image 41 as follows:

image 43, image 42, image 45, image 44, image 47, and image 46.

The further away an image is from the reference image 41, the later it is

transmitted. In this manner, early presentation of an object image is viewable

during the presentation phase while media data is still being transmitted;

therefore, 3D image fidelity increases over time. In general, data that increases pixel or spatial resolution is transmitted progressively later.

#### 10 *Image Display*

After the media is captured, edited, formatted, compressed, and transmitted, an image series display method of the system of the present invention is applied.

Referring now to an embodiment in Fig. 5, which is an illustration of a computer system 57 that is used to play back the images. The computer system 57

includes a computer display 50, a computer camera 51, a keyboard 54 and a mouse 55 (or other pointing device), a joystick 58, and a computer 53 that are electrically connected to each other using standard and known interconnection protocols. As shown in Fig. 6, the computer camera 51 is mounted on or near the computer display 50 such that the user's head 60 is within the field of view of the computer camera 51 while a user's head 60 is positioned to have the computer display 50 within convenient viewing range.



The computer camera 51 is connected to and operated by the computer 53 such that the video signal from the camera 51 is received by the computer 53 for processing. The computer 53 processes the video signal to implement real-time head tracking such that the user's head 60 is actively tracked to determine its relative spatial relationship to the computer display 50. A method of head tracking is discussed in detail in Applicant's U.S. Patent 5,574,836 titled "Interactive Display Apparatus and Method with Viewer Position Compensation" herein incorporated by reference.

Optionally, if the images to be presented are received from a remote location as in the case of a web server (not shown), then a transmission link 56 (such as a modem, Digital Subscriber Line (DSL), cable connection) is connected to the computer 53 such that the compressed and formatted images may be received for presentation.

Next, the presentation method according to an embodiment of the present invention will be detailed. A formatted and compressed image sequence 20 such as those shown in Fig. 2 is received via transmission link 56 and now resident in part or in entirety on the computer 53. The first image to be received is the reference image 21 as shown in Fig. 2. The reference image 21 may be the only image transmitted or it may be the first image of a series of images. If there are no other images available for display, then this image will be selected for display in a view window 52 (see Fig. 5). If only the reference image 21 is sent then the

with the image sequence 20 is initiated. The view window 52 is that area of the computer display 50 in which one of the images in the image sequence 20 is being displayed.

- 5 There are several degrees of movement under which the user's head 60 can be followed. Relative to the computer display 50, these include translation from left to right, translation in and out, head roll from left to right, and head tilt up and down. For the purpose of illustration, translation from left to right is now presented. This is not intended to represent the preferred degree of freedom as
- 10 all degrees contribute to the modeling of a 3D physical representation.

- As the user's head 60 moves from side to side changing rotation angles 61 through 67 as denoted in Fig. 6, a corresponding image relating to the current rotation angle is shown in the view window 52. Assuming now that the user's
- 15 head 60 is at rotation angle 61, the reference image 21 is shown in view window 52. Accordingly, when the user's head 60 position is moved to rotation angle 63, image 23 is displayed. Likewise, for rotation angle 65 results in image 25 displayed, rotation angle 67 results in image 27 displayed, rotation angle 62 results in image 22 displayed, rotation angle 63 results in image 24 displayed,
  - 20 and rotation angle 64 results in image 26 displayed. The actual number of images and the rotation angles used in this example are not intended to be limiting as these values may vary as required for a specific implementation.

In the event that image data transmission is in progress while image data is displayed, then the method presented here will allow interaction with the image sequence 20 prior to receiving individual images. If the preferred image for display is not available then a substitute will be provided until that image is available. For example, if the user's head 60 is now at rotation angle 67 but the corresponding image 27 is not yet transmitted, then the nearest neighbor image will be displayed in the display window 52 in the following order of preference, image 25, image 23, and image 21. Accordingly, this method applies to right side rotation angle images 22, 24, and 26. This method may be extended to other degrees of freedom and view angles as is reflected in a physical modeling of the capture process.

Although the aforementioned embodiment uses head motion to interact with the images, this is not the only possible method of interaction; other body parts may also be tracked to navigate through an image series. Alternatively, more traditional devices such as the mouse 55 or the joystick 58 may be used (see Fig. 5).

Additional attributes that depart from real world simulated viewing are also added to aid in viewing. Examples of these are continuous object rotation, and amplified scaling of an image.

For the case in which only a single image is available for presentation, the distance between the user's head 60 and computer's display 50 as determined by the head tracking software is used to scale the image size. Other head movements such as tilt, roll, and displacement which are normally used to simulate change in view angles are not used in their normal function. These head movements are used to change the position of the image being viewed.

### *Screen Magnification*

Fig. 7 shows a computer display 50 wherein a screen magnification tool 70 is provided according to an embodiment of the present invention. The screen magnification tool 70 can be quickly accessed through highlighting of an icon 71 on the screen which remains in the foreground of the display 50. Accessing the magnification tool 70 is made simpler by requiring only a single highlight of the icon in distinction from the double "mouse click" that has become the industry standard for executing a program.

To allow for more intuitive interaction with the magnification tool 70, magnification power can be revised in the same manner as the tool 70 is used. For example, magnification power of the tool 70 can be increased or decreased through the use of a scroll wheel on a standard mouse. Alternatively, head tracking (as disclosed above) may be used to move the position of magnification tool 70 and also change the magnification power through an action such as forward and backward translation, for example.

In this manner, the magnification tool 70 acts identically to a physical magnification glass. As a result, users will find interaction with the magnification tool 70 simplified as they may interact with the tool 70 just as they would the well-known physical device.

Media presentation consists of receiving the image data, decompressing it, loading it into memory and displaying one of the images that compose media, the selection of that image which is made by the user's head position with respect to the display device. The selection process is done in such a way that the user's view angle with respect to the display is represented by the camera's view angle with respect to the object. This selection process results in enhancing the user's perception of a 3D interactive environment or of viewing a 3D object as opposed to a 2D image of a 3D object.

For example, as the user moves his head to the left, a image showing more of left side of the object image is shown. If the user looks over the top or up, a image representing the angle of the object is shown (provided multiple left-to-right image sequences are captured at media generation time). If the user moves closer to the display, the image is scaled up representing a closer look of the 3D object. If images providing additional resolution are transmitted, then these are presented rather than scaling the image.

## CLAIMS:

1. A method of displaying a series of images according to a user's position relative to a display screen, said display method comprising:

- 5 displaying a first image from the series of images;  
receiving information regarding a change in the user's position relative to the display screen; and  
displaying a second image from the series of images in response to the change in the user's position.

10

2. The method of displaying according to claim 1 wherein the series of images is a series of 2-dimensional images.

3. The method of displaying according to claim 1 wherein the change in the user's position is determined by a change in the user's head position.

15

4. The method of displaying according to claim 3 wherein the second image is an image from the series of images determined by the user's head position where the change in the user's head position is a result of movement selected from the group consisting of left head roll, right head roll, up tilt, down tilt, right translation, left translation, forward translation and backward translation.

20

5. The method of displaying according to claim 4 wherein the right translation and left translation produce a continuous rotation of images in the series of images.

6. The method of displaying according to claim 3 wherein the second image is the first image displayed with new display characteristics.

7. The method of displaying according to claim 6 wherein the new display characteristic for the first image is selected from the group consisting of right translation, left translation, increase in scale and decrease in scale in response to the user's head position where the change in the user's head position is a result of movement selected from the group consisting of right translation, left translation, forward translation and backward translation.

8. The method of displaying according to claim 1 wherein the first image is a center image of the series of images.

9. The method of displaying according to claim 1 wherein if the second image is not available to be displayed then an available image in the series of images closest to the second image is displayed.

10. A method of simultaneously receiving, displaying and interacting with a series of images in response to movement of an interactive device, said display method comprising:

(a) receiving for display a first image from the series of images;

5 (b) receiving for display subsequent images from the series of images;

and

(c) permitting viewing of and interacting with the first image while performing step (b) where interaction with the first image is in response to signals from the interactive device.

10

11. The method according to claim 10 wherein the series of images is a series of 2-dimensional images.

12. The method according to claim 10 wherein the signals from the interactive  
15 device represent movement of the interactive device.

13. The method according to claim 12 further including the step of displaying a second image in response to movement of the interactive device.

20 14. The method according to claim 13 wherein the second image is an image from the series of images determined by the movement of the interactive device where the movement is selected from the group consisting of left movement, right movement, forward movement and backward movement.



15. The method according to claim 11 wherein the right movement and left movement produce a continuous rotation of images in the series of images.

5 16. The method according to claim 10 wherein the interactive device is that of a tracking ball.

17. The method according to claim 10 wherein the interactive device is that of a joystick.

10

18. The method according to claim 10 wherein the interactive device tracks body part movement.

19. The method according to claim 18 wherein the body part being tracked is  
15 the head.

20. The method according to claim 10 wherein the first image is a center image of the series of images.

20 21. The method according to claim 13 wherein if the second image is not available to be displayed then an available image in the series of images closest to the second image is displayed.

22. A method of transmitting a series of images to increase fidelity of transmission, said transmission method comprising:

compressing a selected first image from the series of images;

separately compressing each image from the series of images; and

5 progressively transmitting each compressed image from the series of images in a manner that first transmits the selected first compressed image and then transmits each image from the series of images such that the further each image is from the selected first compressed image the later it is transmitted.

10 23. The method of transmitting according to claim 22 wherein the series of images is a series of 2-dimensional images.

24. The method according to claim 22 wherein the selected first compressed image is a center image in the series of images.

15 25. A computer readable medium having stored thereon computer – executable instructions for displaying a series of images according to a user's position relative to a display screen comprising the steps of:

displaying a first image from the series of images;

20 receiving information regarding a change in the user's position relative to the display screen; and

displaying a second image from the series of images in response to the change in the user's position.

26. A computer readable medium having stored thereon computer –  
executable instructions for simultaneously receiving, displaying and interacting  
with a series of images in response to movement of an interactive device

5 comprising the steps of:

(a) receiving for display a first image from the series of images;

(b) receiving for display subsequent images from the series of images;

and

(c) permitting viewing of and interacting with the first image while

10 performing step (b) where interaction with the first image is in response to signals  
from the interactive device.

27. A computer readable medium having stored thereon computer –  
executable instructions for transmitting a series of images to increase the fidelity

15 of transmission comprising the steps of:

compressing a selected first image from the series of images;

separately compressing each image from the series of images; and

progressively transmitting each compressed image from the series of

images in a manner that first transmits the selected first compressed image and

20 then transmits each image from the series of images such that the further each  
image is from the selected first compressed image the later it is transmitted.

28. A method of increasing the scale of a portion of a displayed object, said method comprising:

providing a perpetual foreground icon for accessing a magnification tool;

accessing the magnification tool;

5 tracking movement of an interactive device;

displaying a specified area as an enlarged area; and

changing an enlargement power in response to the interactive device

while tracking movement and displaying the specified area.

10 29. A computer readable medium having stored thereon computer – executable instructions for increasing the scale of a portion of a displayed object comprising the steps of:

providing a perpetual foreground icon for accessing a magnification tool;

accessing the magnification tool;

15 tracking movement of an interactive device;


displaying a specified area as an enlarged area; and

changing an enlargement power in response to the interactive device

while tracking movement and displaying the specified area.

## ABSTRACT

A method for increasing multimedia data accessibility is presented and more specifically increasing the interactivity with images shown on a display device. A series of images is displayed according to a user's position relative to a display screen by displaying a first image, receiving information regarding a change in the user's position relative to the display screen, and displaying a second image in response to the change in the user's position. The series of images are packaged, compressed and transmitted in a manner that makes it feasible to simultaneously receive, display and interact with the series of images. The scale of a portion of the images is manipulated based on interaction therewith.



**FIG. 1A**  
**(PRIOR ART)**




FIG. 1B




FIG. 2  
(PRIOR ART)




FIG. 4






FIG. 3




FIG. 5




FIG. 6




FIG. 7

COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION

Docket No. 4919

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled Method for Increasing Multimedia Data Accessibility

the specification of which is attached hereto unless the following box is checked:

☐ was filed on \_\_\_\_\_ as United States Application Number or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

\_\_\_\_\_  
(Number)                      (Country)                      (Day/Month/Year Filed)

Yes ☐ No ☐

\_\_\_\_\_  
(Number)                      (Country)                      (Day/Month/Year Filed)

Yes ☐ No ☐

COMBINED DECLARATION & POWER OF ATTORNEY

Docket No. 4919

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below.

\_\_\_\_\_  
(Application Number)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Application Number)

\_\_\_\_\_  
(Filing Date)

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

\_\_\_\_\_  
(Application No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status-patented, pending, abandoned)

\_\_\_\_\_  
(Application No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status-patented, pending, abandoned)

I (we) hereby appoint the following attorney with full power of substitution to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

ALFRED W. BREINER, Reg. No. 18,676; THEODORE A. BREINER, Reg. No. 32,103; and MARY J. BREINER, Reg. No. 33,161.

Address all correspondence to -

BREINER & BREINER, 115 North Henry Street  
P.O. Box 19290, Alexandria, Virginia 22320-0290

Address all telephone calls to -

Mary J. Breiner, Esq. at (703) 684-6885

COMBINED DECLARATION & POWER OF ATTORNEY

Docket No. 4919

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

-----  
Full Name of Sole or First Inventor: \_\_\_\_\_  
(given name, family name) Raymond M. BROEMMELSIEK

Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_

Residence: San Diego, California Citizenship: Canadian

Post Office Address: 9465 Maler Road, San Diego, California 92131  
-----

Full Name of Second Joint Inventor, if any  
(given name, family name) \_\_\_\_\_

Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_

Residence: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Post Office Address: \_\_\_\_\_  
-----

Full Name of Third Joint Inventor, if any  
(given name, family name) \_\_\_\_\_

Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_

Residence: \_\_\_\_\_ Citizenship: \_\_\_\_\_

Post Office Address: \_\_\_\_\_  
-----